



CRANE BASKETS



- **Fully Welded Construction**
- **Self-Closing Swing-In Door**
- **Reinforced Mesh Steel Roof**
- **Hook Point for Crane & Test Weight Attachment**
 - **Fork Pockets for ease of moving**
 - **Tested & Certified**
- **Manufactured by Certified Welders**

CUSTOM MODELS AVAILABLE UPON REQUEST



Crane Baskets are constructed with 2" x 2" square tube throughout.



Labeling of hand signs and data information on all our baskets.



Full perimeter hand rail and (2) harness hook points standard.



Swing-In door is secured with Industrial safety latch.



Fork pockets allow for ease of moving basket. Pockets accept to 2.5x7" forks.



Test Weight quickly attaches to basket with (2) stress-proof rods and hitch pins.

Koke Crane Baskets meet the following regulations:

OSHA 29CFR1910 General Safety Requirements

OSHA 29CFR1926.502 Guardrail System

OSHA 29CFR1926.550 Requirements for Cranes & Derricks

OSHA 29CFR1926.104 Harness Anchors

Part Number	Description	Capacity	Weight
Manbask48C	48"Wx48"Lx98"H	1000lbs.	600
Manbask36C	36"Wx36"Lx98"H	800lbs.	425.00
Manbask96C	48"Wx96"Lx98"H	1,500lbs.	1200