



YARDRAMPS



ALL STEEL CONSTRUCTION

(with SERRATED OPEN DECK FOR HIGH TRACTION)

**PROVIDES GROUND ACCESS TO
TRAILERS AND DOCKS**


EASY TO MOVE AND TRANSPORT

**COST EFFECTIVE WAY TO CREATE
A DOCK**

**DESIGNED FOR SHORT TERM OR
PERMANENT USAGE**

CUSTOM MODELS AVAILABLE UPON REQUEST

RAMP POSITIONER



Our ramp positioner is standard equipment for our yard-ramp. It is designed for moving the yardramp shorter distances (around the yard, etc.) and for positioning the ramp at the trailer or dock. The positioner comes with the slip-on attachment for the forklift as shown in the picture above. The ramp positioner conveniently stores out of the way when not in use.

WHEEL OPTIONS



Two heavy duty solid rubber wheels are standard. A six pneumatic wheel setup is available as an option for rough terrain surfaces.

TOW BAR

The optional tow bar is available for moving the yardramp longer distances (from one warehouse to another in the same complex).

HYDRAULIC PUMP

The double-acting pump quickly raises the yardramp to the desired dock or trailer height. After the ramp is moved to the dock or trailer, simply turn the release knob to lower the ramp into position.

MODEL	CAPACITY	OVERALL WIDTH	USEABLE WIDTH	LENGTH	WEIGHT (LBS.)
16YSD6830	16,000LB.	68"	63"	30'	4,175
16YSD6836L	16,000LB.	68"	63"	36'	5,120
16YSD8030	16,000LB.	80"	75"	30'	4,985
16YSD8036L	16,000LB.	80"	75"	36'	5,850
20YSD6830	20,000LB.	68"	63"	30'	4,385
20YSD6836L	20,000LB.	68"	63"	36'	5,335
20YSD8030	20,000LB.	80"	75"	30'	5,200
20YSD8036L	20,000LB.	80"	75"	36'	6,065
25YSD6830	25,000LB.	68"	63"	30'	4,785
25YSD6836L	25,000LB.	68"	63"	36'	5,770
25YSD8030	25,000LB.	80"	75"	30'	5,615
25YSD8036L	25,000LB.	80"	75"	36'	6,565
30YSD6830	30,000LB.	68"	63"	30'	5,100
30YSD6836L	30,000LB.	68"	63"	36'	6,100
30YSD8030	30,000LB.	80"	75"	30'	6,050
30YSD8036L	30,000LB.	80"	75"	36'	6,900
OPTIONS					
YSD-OPT 01	TOW BAR				
YSD-OPT 03	TANDEM WHEELS				
YSD-OPT 04	NO UNDERCARRIAGE				